

funktel FC5 S

High-end DECT personal emergency signal device with alarm sensor technology and precise localization



FC5 S Medical

FC5 S

- Certified for hazardous workplaces in accordance with DGUV (German Social Accident Insurance) 112-139 and DIN VDE V 0825-1
- Top-located button for Emergency Call Alarms 1 + 2, side-mounted button for Warning Alarms 1 + 2
- Integrated alarm sensors for position, tear-away, loss, no-motion (man down) and time alarms
- Hall sensor for loss alarm
- Localization function via integrated inductive localization receiver
- Localization via Bluetooth localization beacon as well as DECT base stations
- IP 65 protection class: dust-tight and waterjet proof
- Drop resistant up to 1.8 meter
- Interchangeable Li-ion battery, screw-fastened with up to 200 hours of standby time
- Abrasion-resistant, illuminated keypad
- blue.tooth for audio and localization
- Covered socket for audio accessories
- HAC compatible – no audible interference on analog hearing aids
- Software update over-the-air in funktel DoIP systems



Our brand new security handsets for dedicated safety requirements

funktel FC5 S

The professional DECT industrial handset with PES functions



Features

- High-end DECT personal emergency signal (PES) device
- Robust housing, tested for falls of up to 1.8 m
- Illuminated keypad with navigation rocker
- High-quality acoustics for signaling and hands-free use with up to 98 dB (A)*
- Red, easy-to-reach emergency call button
- Side-mounted, freely-assignable warning alarm button (e.g. silent alarm)
- Loss alarm with cord-triggered tear-away contact and Hall sensor (solenoid contact in carry case)
- Automatic alarm triggering via sensors (man down, position and time alarm with pre-alarming)
- Remote control function: triggering of scenarios or pre-programmed calls
- Audio interfaces: blue.tooth and jack
- Vibration alarm
- Data transfer from legacy models via MemCard

Localization/Auxiliary function

- Precise localization of alarm location by means of inductive localization beacons (ILBs)
- Localization via DECT base stations as well as Bluetooth localization beacons.

Optional accessories

- Individual and 6-bay charger for devices or batteries
- Flush-mounted charger for depot and locker systems
- USB programming tool
- MemCard
- Carrying accessories and cases
- Headsets and audio accessories

*) funktel recommends Plantronics Explorer 55 and Sennheiser MB Pro 1.



Sturdy clip and discrete emergency call button

The sturdy, screw-fastened clip ensures that the funktel FC5 S always has optimal support. The discrete buttons for emergency and warning alarms offer a significantly higher level of safety.



MemCard

Network information and contact list data of older-generation devices are copied automatically from the MemCard (optional) to the internal memory. This enables devices to be exchanged easily, even without the intervention of a technician.

Technical data: funktel FC5 S DECT handset

Radio standard:	DECT™ (Digital Enhanced Cordless Telecommunications)
Frequency range:	1.88 ... 1.9 GHz
Transmission power:	Average: 10 mW, peak value: 250 mW
Dimensions:	142 x 46 x 31 mm (incl. clip)
Mass:	Approx. 140 g (incl. battery and clip)
Display:	2" TFT, 64 k colors, 176 x 220 pixels
Keypad:	Abrasion-resistant, illuminated Hardcaps with navigation rocker and softkeys
Address book:	500 local entries, each with name, 2 numbers and comment, central directory (system-dependent)
Call lists:	With 20 entries each for outgoing, received and missed calls
MemCard (optional):	MemCard slot (compatible with FC1 / FC4 / FC11, D3 / D11, and D5 / FC5)
Ring tone volume:	Max. 98 dB (SPL)*, with vibration
Handset operating life**	Talk-time: up to 20 hours Standby: up to 200 hours
Battery type:	Lithium-Ion, 1 200 mAh
Charging time:	Approx. 4 hours typically, approx. 7 hours with empty battery
Operating temperature:	Handset: -10 ... +55 °C Charger: +5 ... +40 °C
Storage temperature:	-25 ... +55 °C (short-term storage, max. 1 month) 0 ... +25 °C (max. 12 months)
Shipping temperature:	-20 ... +60 °C (with battery)
Protection class:	IP 65 (dust-proof and protected against jetted water)
Scope of supply:	Battery, MemCard, charger, plug-in power supply, clip
Part. No.:	5.010.780.300 (gray) / 5.010.780.310 (medical white)

Accessories for funktel FC5 S

Interchangeable battery:	Li-Ion, 1,200 mAh
Carry cases:	Various models – your dealer will be happy to advise

*) Depending on ringtone

**) With fully-charged battery, depending on system settings of the display illumination



funktel GmbH
Windmuehlenbergstr. 20-22
D-38259 Salzgitter

Phone: +49 - 53 41 - 22 35-0
Fax: +49 - 53 41 - 22 35-709
www.funktel.com