

PD-9501G-SFP

PoE Media Convertor, 60W PoE Output

Overview

The Microsemi PD-9501G-SFP is a Media converter with PoE functionality. It has total of 3 ports that can be active simultaneously. Data input can be via SFP module or via the RJ45 port, the output will be data and power up to 60W.

The media converter offers unique solution to power long range installations where the data input comes over fiber. Standard SFP modules can be used (SM or MM modules). The 9501G-SFP complies with IEEE802.3at and will provide PoE after detection, the PoE port will provide the power level needed by the end device offering safe solution for all types of applications starting with 802.3af loads and up to 802.3at 4-pairs loads.

Key Features

- Media converter – SFP to PoE
- Can be used as PoE injector
- All 3 ports can be active simultaneously
- IEEE 802.3at compliant
- Guaranteed output power - 60W
- Supports 10/100/1000Base-T
- Safe: low power devices receive only the power they need



Specifications

Feature	Description
No. of Ports	3 Port 1 : SFP - Data Uplink Port 2 : RJ45 - Data In Port 3 : RJ45 – PoE Out
Data Rates	SFP-100/1000 Mbps Copper-10/100/1000 Mbps
Power over Ethernet Output	Pin Assignment and Polarity: Data Pairs 1/2 (-), 3/6 (+) Spare Pairs 7/8 (-), 4/5 (+) Output Power Voltage: 54Vdc
User Port Power	60 Watts (Guaranteed)
Input Power Requirements	AC Input Voltage: 100 to 240Vac ± 10% AC Input Current: 1.4A @ 100Vac AC Frequency: 50 to 60Hz
Dimensions	80 mm (W) x 36 mm (H) x 160 mm (L)
Weight	0.88 lbs (400 g)
Indicators	System indicator: AC power (Green) Channel power indicator: <ul style="list-style-type: none"> • Green – Power Deliver over 4 pairs • Yellow - Power Deliver over 2 pairs 3 Port data indicators (Green)
Connectors	Shielded RJ-45, EIA 568A and 568B SFP cage
Environmental Conditions	Operating Ambient Temperature: 14° to 113°F (-10°C to 45°C) @60W 14° to 131°F (-10°C to 55°C) @30W Operating Humidity: Maximum 95%, Non-condensing Storage Temperature: -4° to 158°F (-20° to 70°C) Storage Humidity: Maximum 95%, Non-condensing
Reliability	MTBF: 150,000 hrs. @ 25°C
Warranty	1-year
Regulatory Compliance	RoHS Compliant, WEEE Compliant, CE IEEE 802.3at (PoE)
Electromagnetic Emission & Immunity	FCC Part 15, Class B EN 55022 Class B (Emissions) EN 55024 (Immunity) VCCI
Safety	UL/EN/IEC 60950-1

PD-9501G-SFP

PoE Media Convertor, 60W PoE Output

Ordering Information

Microsemi P/N	Name	Description
PD-9501G-SFP/AC	Microsemi 9501G-SFP	PoE Media Convertor, 60W



Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.



Microsemi Corporate Headquarters
 One Enterprise, Aliso Viejo, CA 92656 USA
 Within the USA: +1 (800) 713-4113
 Outside the USA: +1 (949) 380-6100
 Sales: +1 (949) 380-6136
 Fax: +1 (949) 215-4996
 email: sales.support@microsemi.com
www.microsemi.com

Microsemi Corporation (MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense & security, aerospace and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 3,600 employees globally. Learn more at www.microsemi.com.

©2015 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.