

# PD-9001-10GR Midspan

## Single Port, 10GbE, 30W PoE Indoor Midspan

### Key Features

- IEEE 802.3at compliant
- IEEE 802.3af backward compatible
- Guaranteed output power - 30W
- Supports 10/100/1000Base-T & 10GbE
- Safe: low power devices receive only the power they need
- Automatic Detection and Protection of non-standard Ethernet terminals
- Compact design fits easily in WLAN Access Point and IP Cameras installation

### Overview

The Microsemi PD-9001-10GR is a single port, high-power solution for remote powering of current and emerging high power indoor applications. Generating 30W, the PD-9001-10GR enables remote power for a new range of applications including 802.11ac Access Points, pan-tilt-zoom (PTZ) cameras and video-phones. It complies to IEEE 802.3at PoE standard and is backward compatible to IEEE802.3af. It can power both existing 10/100/1000Base-T network devices and emerging wireless 10GbE devices such as wireless IEEE 802.11ac access points.



Figure 1: PD-9001-10GR

### Specifications

Feature	Description
No. of Ports	1
Data Rates	10/100/1000 Mbps & 10GbE
Power over Ethernet Output	Pin Assignment and Polarity: 4/5 (+), 7/8 (-) Output Voltage: 55Vdc
User Port Power	30 Watts (Guaranteed)
Input Power Requirements	AC Input Voltage: 90 to 264Vac AC Input Current: 1.5A @ 100-240Vac AC Frequency: 50 to 60Hz
Dimensions	87.9mm (W) x 43mm (H) x 166mm (L) 3.46 in. x 1.68 in. x 6.53 in
Weight	0.91 lbs (410 g)
Indicators	AC Power (Yellow)
	Channel Power (Green)
Connectors	Shielded RJ-45, EIA 568 A and 568 B
Environmental Conditions	Operating Ambient Temperature: 14° to 113°F (-10 to 45°C) @ 30 W
	Operating Humidity: Maximum 90%, Non-condensing
	Storage Temperature: -4° to 158°F (-20° to 70°C)
	Storage Humidity: Maximum 95%, Non-condensing
Reliability	MTBF: 350,000 hrs. @25°C
Warranty	1-year
Regulatory Compliance	IEEE 802.3at (PoE), RoHS Compliant, WEEE Compliant, CE
Electromagnetic Emission & Immunity	FCC Part 15, Class B EN 55022 Class B (Emissions) EN 55024 (Immunity) VCCI
Safety	UL/EN/IEC 60950-1

## Ordering Information

Part Number	Name	Description
PD-9001-10GR/AC	Microsemi 9001-10GR	1-Port 10GbE, 30W PoE Midspan

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.



Microsemi Corporate Headquarters  
One Enterprise, Aliso Viejo, CA 92656 USA  
Within the USA: +1 (800) 713-4113  
Outside the USA: +1 (949) 380-6100  
Sales: +1 (949) 380-6136  
Fax: +1 (949) 215-4996  
email: [sales.support@microsemi.com](mailto:sales.support@microsemi.com)  
[www.microsemi.com](http://www.microsemi.com)

Microsemi Corporation (MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense & security, aerospace and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 3,600 employees globally. Learn more at [www.microsemi.com](http://www.microsemi.com).

©2015 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.